



Shandong Chik Bearing Co., Ltd.



INA SCE912 needle roller bearings

Bearing No. SCE912

SCE912 Bearing 2D drawings and 3D CAD models

| | |
|-------------------|---|
| Size | 14.288x19.05x19.05 mm |
| Bore Diameter | 14,288 mm |
| Outer Diameter | 19,05 mm |
| Width | 19,05 mm |
| F _w | 9/16 inch |
| F _w | 14,288 mm |
| D | 0,75 inch |
| D | 19,05 mm |
| C | 0,75 inch |
| C | 19,05 mm |
| m | 0,026 lbs / Weight |
| m | 12 g / Weight |
| C _r | 2410 lbf / Dynamic load rating (radial) |
| C _r | 10700 N / Dynamic load rating (radial) |
| C _{0r} | 3690 lbf / Static load rating (radial) |
| C _{0r} | 16400 N / Static load rating (radial) |
| n _G | 17600 1/min / Limiting speed |
| n _B | 12000 1/min / Reference speed |
| Category | Needle Non Thrust Roller Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SCHAEFFLER GROUP |



Shandong Chik Bearing Co., Ltd.

| | |
|---------------------------|---|
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.01 |
| Product Group | B04144 |
| Rolling Element | Needle Roller Bearing |
| Component | Roller Assembly with Outer Ring - No Inner Ring |
| Enclosure | Open |
| Self Aligning | No |
| Retainer | Yes |
| Number of Rows of Rollers | Single Row |
| Separable | No |
| Closed End | No |
| Inch - Metric | Inch |
| Relubricatable | No |
| Thrust Bearing | No |
| Long Description | 9/16" Bore; 3/4" Outside Diameter; 3/4" Width; Needle Roller Bearing; Roller Assembly with Outer Ring - No Inner Ring; Open; Not Self Aligning; Retainer; Single Row of Rollers; Not Sepa |
| Other Features | 2 Rib Outer Ring Drawn Cup Bearing Steel Cage |
| Category | Needle Non Thrust Roller Bearing |
| UNSPSC | 31171512 |
| Harmonized Tariff Code | 8482.99.65.30 |
| Noun | Roller Assembly with Outer Ring |
| Keyword String | Bearing Needle |
| Manufacturer URL | http://www.luk-us.com |
| Manufacturer Item Number | SCE912 |
| Weight / LBS | 0.026 |
| Outside Diameter | 0.75 Inch 19.05 Millimeter |



Shandong Chik Bearing Co., Ltd.

| | |
|-------|------------------------------|
| Width | 0.75 Inch 19.05 Millimeter |
| Bore | 0.563 Inch 14.3 Millimeter |